

D-LFA / D-LFB

IP65



D-LFB9



D-LFK9





D-LFA4






D-LFA3

D-LFK3

12°



Special lighting system designed with high efficiency LED technology within range of 3 to 9 W for outdoor applications. Can also be employed in architectural garden lighting, tree lighting and for highlighting details.

Durability in all kinds of outdoor conditions thanks to corrosion-resistant cast aluminum outer body thereof. Two different types of mounting options are offered. The models include the type with foot anchored to the ground and the type with foot driven into the ground.

D- LFA3

D- LFA3 and D- LFA4 dimensions are the same.



D- LFK9



| Code | D-lfa3 / D-lfk3 | D-LFA4 / D-LFK4 | D-LFB9 / D-LFK9 |
|--------------------|---|--------------------------|-----------------|
| LED | High efficient Power LED | | |
| System Power | 4 W | 5,5 W | 12 W |
| Light Flux | 260 lm | 350 lm | 800 lm |
| Colour Temperature | 3000 - 4000 - 5000 K, R-G-B - Amber | | |
| Voltage | 220V - 50Hz | | |
| Body | Aluminum injection painted with electrostatic paint | | |
| Cooler | Cooling from the body surface | | |
| Lens Angle | 12°, 25°, 29°, 61° Lens | | |
| Glass | 3 mm thickness tempered | | |
| Colour | Grey | | |
| Box Dimensions | 15x15x20cm 15x15x30cm | 15x15x20cm 15x15x30cm | 18x18x25cm |
| Weight | 800 gr | 800 gr | 1.590 gr |