


Linear Lighting

DFR

IP20



DFR 20




DFR 60

DFR 80

DFR fixtures which can be used as surface mounted and pendant are produced in 19 - 60 - 80mm width. They can be used as a single profile up to approximately 2.5 meters length in linear applications. They can be attached end to end and be used as a continuous light source. Height of the pendant can be easily adjusted thanks to spring mounting parts.



Code	a	b	c
DFR 20/100	1000mm	19mm	16mm
DFR 20/120	1200mm	19mm	16mm
DFR 20/150	1500mm	19mm	16mm
DFR 60/100	1000mm	60mm	85mm
DFR 60/120	1200mm	60mm	85mm
DFR 60/150	1500mm	60mm	85mm
DFR 80/100	1000mm	80mm	85mm
DFR 80/120	1200mm	80mm	85mm
DFR 80/150	1500mm	80mm	85mm



Code	DFR 20/100 DFR 20/120 DFR 20/150	DFR 60/100 DFR 60/120 DFR 60/150	DFR 80/100 DFR 80/120 DFR 80/150
LED	High efficient Mid-Power LED		
System Power	15 W 18 W 27 W	30 W 36 W 45 W	30 W 36 W 45 W
Light Flux	1,400 lm/m 1,680 lm/m 2,100 lm/m	2,800 lm/m 3,360 lm/m 4,200 lm/m	2,800 lm/m 3,360 lm/m 4,200 lm/m
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	Aluminum extrusion body and painted with electrostatic powder paint.		
Diffuser	2,8 mm thick prismatic lens		
Colour	White or Grey		
Weight	500 gr 600 gr 750 gr	3000 gr 3750 gr 4500 gr	3400 gr 4100 gr 5200 gr