



ELD 75



Rotatable



Ø 90mm




Ø 90mm

Ø 80mm

IP20

Code	ELD 75/5	ELD 75/8
LED	High Efficiency Power LED	
System Power	5 W	9,5 W
Light Flux	450 lm	850 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Aluminum injection	
Cooler	Aluminum	
Reflector	Aluminum	
Glass	3mm thick transparent tempered	
Box Dimensions	12x12x12 cm	
Weight	290 gr	
Cut-Out	Ø 75 mm	

ELD 125



Rotatable



Ø 138mm




Ø 138mm

Ø 110mm

IP20

Code	ELD 125
LED	High Efficiency COB LED
System Power	16 W
Light Flux	1.060 lm
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	Aluminum injection
Cooler	Aluminum
Reflector	Aluminum
Glass	3mm thick transparent tempered
Box Dimensions	15x15x15 cm
Weight	740 gr
Cut-Out	Ø 125 mm

ML 110

cd/klm
— C0 - C180 — C90 - C270

Ø 119mm

110mm

IP20

Code	ML 110
LED	High Efficiency COB LED
System Power	5 - 13, 27 W (active cooling)
Light Flux	480 - 1300 - 2760 lm
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	Aluminum injection
Reflector	Aluminum
Cooler	5-13W (passive), 27W (active cooling)
Diffuser	Tempered glass, transparent
Box Dimensions	16x16x15 cm
Weight	850 gr
Cut-Out	Ø 110 mm