

FSA IP40



FSA series products which can be mounted vertically or horizontally on the wall thanks to the minimalist and cornered structure thereof create a dynamic atmosphere in the areas they are used. They are manufactured in a manner to give light in a double or single-sided (both up and down, or only below or above) way. Opal diffusers have been used in order that the fixtures can give light in a pleasant way by not making the eyes tired.



| Code | | | |
|----------|----------|--|--|
| FSA 1x18 | 610 mm | | |
| FSA 2x18 | 610 mm | | |
| FSA 1x36 | 1.210 mm | | |
| FSA 2x36 | 1.210 mm | | |

| Code | FSA118 | FSA218 | FSA136 | FSA236 |
|--------------------|---|----------|------------|----------|
| LED | High efficient Mid-Power LED | | | |
| System Power | 1x18W | 2x18W | 1x36W | 2x36W |
| Light Flux | 1680lm | 2x1680lm | 3360lm | 2x3360lm |
| Colour Temperature | 3000 - 4000 - 5000 K | | | |
| Voltage | 220V - 50Hz | | | |
| Body | 1 mm thick DKP sheet steel and 80 micron thick electrostatic powder paint | | | |
| Diffuser | 5 mm thick opal | | | |
| Colour | Grey | | | |
| Box Dimensions | 8x63 | x9 cm | 8x123x9 cm | |
| Weight | 3.00 | 0 gr | 6.00 |) gr |