


MDL IP65






MDL projectors are the most suitable solution for various outdoor lighting projects thanks to their high efficiency and various power(W) options. There are types with high luminous flux and lens types at angles suitable for the area to be illuminated.

The luminaires are easily mounted with the foot mechanism. When it is brought to the desired angle, the spring and gear mechanism fully locks the armature. In this way, angle shifts are prevented over time.







Code	а
MDL4	590 mm
MDL3	500 mm
MDL2	410 mm
MDL1	240 mm

				16°	_		_		60°
75°		Λ		75°	75°		\triangle		759
60°		45000		60°	60°	\times	8000	X	60°
45°		67500		45°	45°	$\geq \downarrow$	12000		459
		90000			\checkmark		16000		
30°	15°	0°	15°	30°	30°	15°	0°	15°	30°

Code	MDL4	MDL3	MDL2	MDL1			
LED	High Efficiency Power Led						
System Power	200W	150W	100W	50W			
Light Flux	21.000 lm	16.000 lm	10.800 lm	5.500 lm			
Color Temperature	3000 K 4000 K 5000 K						
Voltage	220V - 50Hz						
Body	Aluminum						
Cooler	Aluminum injection						
Diffuser	Clear polycarbonate						
Weight	9.700 gr 8.100 gr 6.500 gr						